



Gelida

INTELLIGENT INNOVATION OF LIQUID NITROGEN TANKS

Gelida 47: Intelligent, integrated liquid nitrogen storage ecosystem with 24/7 monitoring



GELIDA 47

Liquid Nitrogen Storage Ecosystem



Real-time monitoring for temperature and LN2



Patient and sample tracking software enabling remote alarm



One or Two-Person Access Authentication





Instant audio, visual and digital alarms



Mobile Tank Management with PDA & App



Centralized management via BaseStation software

Model

Gelida 47 for Straws Gelida 47 for Vials

Battery life

Min 10 days*

Capacity

47 L (10 canisters / 6 box racks)

Touch screen

5 inch color touch display

Net weight Approx 30 kg

Storage temperature -196° C Liquid Phase LN2

^{*}Note: Battery life may be longer depending on access frequency, alarms and battery health.

Enhanced Security:

- · Single or dual person authenticated tank access.
- · Alerts via audio, visual and BaseStation App notification.
- Gelida 47 notifies you via SMS and/or Phonecall in case of an alarm when using the Basic software.

Peace of Mind:

- · Real time monitoring and reporting of tank fleet status with BaseStation.
- · Automatic logging of tank access, alarms and warnings.

Connected Control:

- · Mobile management with PDA and App.
- · Centrally manage storage via BaseStation link to Gelida Ecosystem devices.

Wireless:

 Lid designed with quick swap battery, WiFi and integrated digital temperature sensors reducing external wiring.

Dual Sensors:

• Two temperature sensors within the tank enables temperature monitoring and estimation of LN2 levels.

Convenience:

- Touchscreen enables in person access, and quick recall tank condition and status.
- · Gelida 47 displays the remaining liquid nitrogen level on the tank lid.
- Rolling wheel base with lockable wheels enables tank to be moved easily while full.



GELIDA 47 CONFIGURATIONS

MODEL	GELIDA 47 (STRAWS)	GELIDA 47 (VIALS)				
Capacity (L)	47					
Bare weight	66 Lbs (30 +/- 3kg)					
Full weight	158	Lbs (~68 kg)				
Neck Diameter	5 inc	ch (127 mm)				
Outer diameter	21.25 inch	(Approx 540 mm)				
Height	30.9 inch	(Approx 785 mm)				
Storage Container Type For the straws, LxDiameter and vials DxWxH	Canister 10.95 x 2.83 inch 278 x 72 mm	Rack 5 boxes/rack 3.07 x 3.07 x 2.32 inch Box Size 78 x 78 x 59 mm				
Amount	10	6				
Screen size	5.0-inch colour 1280 $ imes$ 720 capacitive multi touch					
Power supply	Battery: 5VDC Lithium Polymer Battery Charging Adapter: 100-240V~,50/60Hz,0.5A					
Unlocking mode	Digital password lock (single/dual authentication) Emergency access key					
Operation log	Autom	natic Recording				
Alarms	Abnormal temperature Low battery/loss of electricity Excessive tank open time					
Mode of data transmission	WiFi 802.11b/g/n AES-256 encryption algorithm					
Number of temperature sensors	2 High position and Low position within tank dewar					

PRODUCT NAME	ТҮРЕ	CONFIGURATION		
Gelida 47 (Straws)	Instrument	10 Canisters		
Gelida 47 (Vials)	Instrument	6 Racks		
Gelida 47 Battery	Accessory	1 Spare Battery		

Specifications for all markets are subject to regulatory approval and final product release.

GELIDA 47 BASESTATION SYSTEM

GELIDA BASESTATION SOFTWARE

All your cryotank information, visualized in one place. Centralized management and monitoring enables quickly view the temperatures, capacity, battery level, and alarms. Through the interface devices can be remotely controlled and located; features include remote single/batch unlocking, and find my tank.

Through the interface, devices can be remotely controlled and located; features include remote single/batch unlocking and find my tank.



BASESTATION APP

Remote Monitoring & digitized alerts.

The BaseStation APP can be installed on Android mobile devices, enabling faster notification and response when abnormal conditions arise. Remotely view tank status, such as tank temperature, capacity, notification and alarm information.



GELIDA BASESTATION PDA

BaseStation features in the palm of you hand.

The BaseStation PDA is a BaseStation Workstation you can take with you. Enabling all monitoring functions, but additionally adding tank control functions and sample management functionality. Create sample deposit and withdrawal orders, and identify sample location on the screen; the inbuilt precision saves time and supports error reduction efforts.





Device Management: Add, remove or edit basic device information, view tank capacity, tank status information, alarms, and retrieve access/operation records.

											0
111.		-	-			-	-	-	damen .		AND
	-	-		-	-				-		-
	***	200.00		-	-		-			-	-
		-			-	-	-				7500
	Assessment.	2000			-	90	811				depart
	Signal continue	1000			-	80	84		District to the	-	-
	Parameters.	1000		-	-					2004200	7990
	A majoritation.	trees on		-	-		- 10			20040-00	
	-	100.0		-	-					-	
	Albert control	Contract.			-	-	146		manuscript and the same		_

Sample Status: Book in deposit and withdrawal orders, select where to store a single sample, which samples to take out, and record all access statistics for tracability.

The same	income.		1000	neres			
	\$1.00	100000				Delicher.	
to .	0.00	000	Destroit date	-	0.0.6w	5000	
-	-	-		-		Section .	
-	0.00	1000	-	-	100000	minutes:	
-	1.000	100000			100000	100,000	
-	terms.	-	interest to the	-		MOTO SALARITY	
46	4000	And to its assessment	deposits (sele-	\$1000 pt 1000 pt		0.000	
- 10	6100	-	-	March 19 (19 (19 (19 (19 (19 (19 (19 (19 (19		0000	
-	6mm	-	fanomer team	Bioch + 0.0 (1000/000	
PROFES.	pripe	-	department of the		-	*****	
1000	8000	-		100000-0000		September 1	
1000			bearing to the	market and	10.000		

Alert Information: You can view the alarm status of all devices, including the device name, alert time, location, alert content, if a notification has been issued, alarm history, and whether the alarm is resolved. Gelida 47 notifies you via SMS in case of an alarm when using the Basic software.

evice user	***				0.0
	- market market	-	realization.	-	
	-	900-0	000000	******	NAME AND ADDRESS OF THE OWNER, WHEN
	- 100		0.00	SHATTE .	-
	-		00000		tell property free
	-	0000	000000		tiple columns of the
	-	000-0	0004509	\$660.00	may be a series from
	-	000-0	40444	2010/01/02	And Discourse from
	- 01		0.000	2000-02	tell passent his
	44	(max)	2004.040	0000000	the second less
A IN		986-8	000-0-0-00	2010/01/02	the second her
		Selection.	300000	Shees	bill blewed bill
	-	200-2	1000000	*****	THE DESCRIPTION NAMED

User Management: Manage authorized users for all tanks in a central location. User names and passwords can be updated, deleted, and synced to all connected tanks.



Single Sample Tracking: Patient and sample information can be viewed and filtered, using name, gender, freezing time, sample unique ID, with traceability down to location where a single sample is stored within a tank.



Simplified Visuals: Quickly view the temperatures, capacity, battery level, alarms. Simplified visual interface allows for devices can be remotely controlled and quickly located; features include remote single/batch unlocking, and "Find My Tank". Gelida 47 displays the remaining liquid nitrogen level on the tank lid.



Final appearance of features are subject to change; may vary depending on specific customer implementations, version of software and lab integrations.

Gelida 47 BaseStation
System enables your lab
to manage Gelida
Ecosystem Cryostorage
Tanks and precious
samples, all within one
centralized digital
platform.





Please refer to the instructions for use.

For further information, please contact your Service Representative or visit:

www.geneabiomedx.com